LF410
Low-density polyethylene (LDPE)

General Information
LF410 is an Low-density polyethylene resin produced in the tubular process, Designed for film, foamed and has excellent processability, excellent optical properties, and mechanical properties

Key Features
- Excellent processability and mechanical properties
- Excellent optical properties
- Low Fish Eye
- Contains a low amount of slip agent and antiblock agent

Applications
- General Blown film, Foamed

Properties

	Item		Measuring Method	Value	Unit
Physical	Melt Flow Index (190℃, 2.16kg)		ASTM D1238	2.0	g/10min
	Density		ASTM D1505	0.922	g/cm^3
Film (50㎛)	Tensile Strength (Break)	MD	ASTM D882	250	kgf/cm^2
		TD		210	kgf/cm^2
	Elongation (Break)	MD	ASTM D882	250	%
		TD		600	%
	Dart Drop Impact Strength, F50		ASTM D1709	90	g
	Haze		ASTM D1003	< 8	%
Thermal	Melting Point		LC Method	110	℃
	VICAT Softening Point		ASTM D1525	93	℃

• NOTE : Physical Properties : these are not to be construed as specifications

• Process Condition : Temperature : 170℃, BUR : 2.5, Film Thickness 50㎛

* Disclaimer: All information in this document is for reference only and is not a final product specification. Before using our products, the customer must determine for himself the suitability, safety and legality of the intended use. We do not assume any liability or responsibility for the use of this document or the contents of this document, and we reserve the right to change the contents of this document arbitrarily without prior notice.