JG SUMMIT OLEFINS CORPORATION

Better Life Through Innovation

Provisional Product Data Sheet
UHF1050A (Developmental Grade)

UHF1050A is a high molecular weight high density polyethylene grade suitable for blown film applications.

Property	Test Condition	Test Method	Typical Value	Unit
Flow Index	190°C / 21.6 kg	ASTM D1238	10	g/10 min
Density	23 °C	ASTM D792	0.950	g/cm^3

FEATURES:

- Outstanding puncture resistance
- Superior toughness
- Good stiffness
- High moisture barrier properties

TYPICAL APPLICATIONS:

- Grocery bags
- Supermarket produce bags
- Carrier bags
- Trash bags
- Sack liners

DISCLAIMER:
Information provided herein is given for general purposes only. It is the customer's sole responsibility to test the product and any information provided herein to determine whether they are suitable for the customer's purposes. JGSOC MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. Customers are strongly advised to review the applicable Material Safety Data Sheet before handling or using the products described herein.

Revision Date: 28 June 2022

JGSOC © 2022 Rev. 0

9F-11F Robinsons Cyberscape Gamma Bldg.
Topaz and Ruby Roads, Ortigas Center
Brgy. San Antonio, Pasig City, 1605 Philippines

+632 8 230 5000 / +632 8 397 3200

+632 8 395 2674

www.jgspetrochem.com