JG SUMMIT OLEFINS CORPORATION

Better Life Through Innovation

Provisional Product Data Sheet
UHJ0860A (Developmental Grade)

UHJ0860A is a high density polyethylene injection molding grade with good processability. This grade contains UV stabilizer for protection against outdoor conditions.

Property	Test Condition	Test Method	Typical Value	Unit
Melt Index	190°C / 2.16 kg	ASTM D1238	8.0	g/10 min
Density	23 °C	ASTM D792	0.960	g/cm^3

FEATURES:

- High stiffness
- Good impact strength
- UV stabilized

TYPICAL APPLICATIONS:

- Crates and cases
- General-purpose injection molded articles

DISCLAIMER:
Information provided herein is given for general purposes only. It is the customer's sole responsibility to test the product and any information provided herein to determine whether they are suitable for the customer's purposes. JGSOC MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. Customers are strongly advised to review the applicable Material Safety Data Sheet before handling or using the products described herein.

Revision Date: 14 January 2022

JGSOC © 2022 Rev. 2

9F-11F Robinsons Cyberscape Gamma Bldg.
Topaz and Ruby Roads, Ortigas Center
Brgy. San Antonio, Pasig City, 1605 Philippines

+632 8 230 5000 / +632 8 397 3200

+632 8 395 2674

www.jgspetrochem.com